



Risk Control at UFG Insurance | riskcontrol@unitedfiregroup.com | 800-828-2705

## Machine guarding

SAFETY CHECKLIST	YES	NO	NEEDS IMPROVEMENT
Is there a training program to instruct employees on safe methods of machine operation?			
Is there adequate supervision to ensure that employees are following safe machine operating procedures?			
Is there a regular program of safety inspection of machinery and equipment?			
Is all machinery and equipment kept clean and properly maintained?			
Is sufficient clearance provided around and between machines to allow for safe operations, set up and servicing, material handling and waste removal?			
Is equipment and machinery securely placed and anchored to prevent tipping or other movement that could result in personal injury?			
Is there a power shut-off switch within reach of the operator's position at each machine?			
Can electric power to each machine be locked out for maintenance, repair or security?			
Are foot-operated switches guarded or arranged to prevent accidental actuation by personnel or falling objects?			
Are manually operated valves and switches controlling the operation of equipment and machines clearly identified and readily accessible?			
Are all emergency stop buttons colored red?			
Are all pulleys and belts within 7 feet (2.1336 meters) of the floor or working level properly guarded?			
Are all moving chains and gears properly guarded?			
Are splash guards mounted on machines that use coolant to prevent the coolant from reaching employees?			
Are methods provided to protect the operator and other employees in the machine area from hazards created at the point of operation, ingoing nip points, rotating parts, flying chips and sparks?			
Are machine guards secure and arranged so they do not cause a hazard while in use?			
If special hand tools are used for placing and removing material, do they protect the operator's hands?			
Are revolving drums, barrels and containers guarded by an enclosure that is interlocked with the drive mechanism so that revolution cannot occur unless the guard enclosure is in place?			
Do arbors and mandrels have firm and secure bearings, and are they free from play?			
Are provisions made to prevent machines from automatically starting when power is restored after a power failure or shutdown?			
Are machines constructed so as to be free from excessive vibration when the largest size tool is mounted and run at full speed?			
If machinery is cleaned with compressed air, is air pressure controlled and PPE or other safeguards utilized to protect operators and other workers from eye and body injury?			





Risk Control at UFG Insurance | riskcontrol@unitedfiregroup.com | 800-828-2705

## Machine guarding

SAFETY CHECKLIST	YES	NO	NEEDS IMPROVEMENT
Are fan blades protected with a guard having openings no larger than 1/2 inch (1.2700 centimeters) when operating within 7 feet (2.1336 meters) of the floor?			
Are saws used for ripping equipped with anti-kickback devices and spreaders?			
Are radial arm saws so arranged that the cutting head will gently return to the back of the table when released?			
If the power disconnect for equipment does not also disconnect the electrical control circuit, are the appropriate electrical enclosures identified and is a means provided to ensure that the control circuit can also be disconnected and locked out?			
Is the locking out of control circuits instead of locking out of main power disconnects prohibited?			
Are all equipment control valve handles provided with a means for locking out?			
Does the lockout procedure require that stored energy (mechanical, hydraulic, air, etc.) be released or blocked before equipment is locked out for repairs?			
Are appropriate employees provided with individually keyed personal safety locks?			
Are employees required to keep personal control of their key(s) while they have safety locks in use?			
Is it required that only the employee exposed to the hazard can place or remove the safety lock?			
Is it required that employees check the safety of the lockout by attempting a startup after making sure no one is exposed?			
Are employees instructed to always push the control circuit stop button prior to re-energizing the main power switch?			
Is there a means provided to identify any or all employees who are working on locked-out equipment by their locks or accompanying tags?			
Are a sufficient number of accident prevention signs or tags and safety padlocks provided for any reasonably foreseeable repair emergency?			

## **COMMENTS/RECOMMENDATIONS:**

## **COMPLETED BY:**

DATE:

This form, supplied by UFG Insurance, merely provides minimum guidelines for you to follow and may be utilized as a tool for fact-gathering purposes to assist in your investigation. The information requested above is not exhaustive and you should, at your own discretion, request any necessary additional information as the specific situation may warrant.